

## Flowcoat LXP

A solvent free, high performance, flexible polyurethane coating system for use on substrates such as concrete, wood, metal and asphalt.

Provides a coloured, seamless finish for alternative substrates.



### Flexible:

Provides a degree of flexibility to allow application onto alternative substrates.



### High Impact Resistance

Offers excellent protection against dropped items and heavy loads.



### Solvent Free:

Solvent free, low in VOCs and environmentally friendly.



### Hygienic & Easy to Clean:

The seamless and gloss finish allows the system to be cleaned easily.



### Slip Resistant (optional)

Slip resistant finish may be tailored to meet specific client requirements.



Forest Green



Tile Red



Ocean Blue



Goosewing Grey



Warm Grey



Dark Grey

The applied colours may differ from the examples shown.  
For a full colour chart and samples, contact your local Flowcrete office.



## Technical Profile\*

### FIRE RESISTANCE

EN 13501-1

B<sub>fl</sub> - s1

### SLIP RESISTANCE\*\*

Method described in BS 7976-2 (typical values for 4-S rubber slider)

Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)

### THERMAL RESISTANCE

Tolerant up to 60°C

### WATER PERMEABILITY

Nil – Karsten test (impermeable)

### CHEMICAL RESISTANCE

Contact technical department

### SURFACE HARDNESS

55 (Shore D)

### ABRASION RESISTANCE

BS 8204-2

Grade AR2 Medium Duty Industrial and Commercial

### FLEXURAL STRENGTH

BS 6319

> 15 N/mm<sup>2</sup>

### TENSILE STRENGTH

BS 6319

> 10 N/mm<sup>2</sup>

### BOND STRENGTH

Greater than cohesive strength of 25 N/mm<sup>2</sup> concrete. > 1.5 MPa

### ELONGATION AT BREAK

BS 6319

60%

### SPEED OF CURE

10 °C

20 °C

30 °C

Light Traffic

48 h

16 h

12 h

Full Traffic

72 h

48 h

40 h

Full Chemical Cure

12 d

7 d

6 d

\* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.


\*\*The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance, longer-term wear and/or surface contaminants (wet or dry). Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

## Model Specification

<b>System</b>	Flowcoat LXP
<b>Finish</b>	Gloss
<b>Thickness</b>	Dependent on specification
<b>Manufacturer</b>	Flowcrete Asia

Preparatory work and application in accordance with manufacturer's instructions.

## System Design



## Products Included In This System

<b>Primer</b>	Flowprime LXP
<b>Finishing Coat</b>	Flowcoat LXP

For actual coverage rates, refer to the appropriate project specification.

Detailed application instructions are available upon request.

## Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm<sup>2</sup>, free from laitance, dust and other contamination. The substrate should be dry up to 75% RH as per BS8204 and free from rising damp and ground water pressure.

## Installation Service

The installation should be carried out by a licensed contractor with a documented quality assurance scheme. For details of our licensed contractors, contact our customer service team or enquire via our website at [www.flowcreteasia.com](http://www.flowcreteasia.com)

## Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

## Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

## Important Note

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages.

## Further Information

To ensure you are specifying a fit-for-purpose floor, please consult our Technical Advisors or visit our website to register your interest in specifying one of the most durable floors on the market.

1. Light colours may require additional coats to achieve desired results 2. It is recommended that top coat colours are close to base coats colours to achieve desired results 3. This product is not UV stable and may discolour unless otherwise stated 4. System Data Sheet to be read in conjunction with Method Statement and Product data Sheets.