



# EVERCLEAR VOX

ACRYLIC CURE & SEAL FOR DECORATIVE CONCRETE

EUCLID CHEMICAL

CURING & SEALING

## DESCRIPTION

**EVERCLEAR VOX** is a water-based pure acrylic sealer for concrete with excellent blush resistance and total resistance to yellowing from UV exposure. This sealer imparts an attractive, low gloss and protection to all concrete surfaces, and is especially suited for decorative concrete. **EVERCLEAR VOX** dries to a clear, matt finish, but a higher gloss can be achieved with additional coats.

## PRIMARY APPLICATIONS

- Concrete driveways, sidewalks, floors
- Stamped, stenciled, coloured, acid stained concrete
- Concrete pavers and precast units
- Cultured stone

## FEATURES / BENEFITS

- Non-yellowing, medium gloss sealer provides protection and improved appearance to concrete
- Low odour
- Excellent abrasion and blush resistance
- Can be applied over previous coats of sealers – water based and solvent based
- Excellent recoatability

## TECHNICAL INFORMATION

<b>Viscosity, cp:</b>	5	<b>% Solids (by Weight):</b>	>25%
<b>Colour:</b>	Milky White (wet) Crystal Clear (dry)	<b>Weatherometer Cycling @ 100 Hours:</b>	No yellowing or loss of gloss
<b>Dry to Touch:</b>	Less than 1 hour	<b>Resistance to Gasoline, Brake Fluid, Solvents:</b>	Poor
<b>Foot Traffic:</b>	4 to 6 hours	<b>Resistance to Acids/Alkalies:</b>	Moderate
<b>Wheel Traffic:</b>	6 to 10 hours	<b>Blush Resistance:</b>	Excellent

\*Slight blushing, or whitening of the sealer film, is possible during the first one or two wetting and drying cycles after sealer application. Likelihood of blushing is increased when the **EVERCLEAR VOX** surface becomes wet before the sealer has fully dried. This initial blushing is fully recoverable when the source of water is gone. Fully dried **EVERCLEAR VOX** is extremely blush resistant.

## SHELF LIFE

2 years in original, unopened container

## SPECIFICATIONS / COMPLIANCES

- ASTM C 1315 (excluding water retention)
- ASTM C 309, Type 1, Class A & B

## PACKAGING

**EVERCLEAR VOX** is packaged in 20 L jerry cans and 200 L plastic drums.

EVERCLEAR VOX

MASTER FORMAT #:  
03 39 23

## COVERAGE

---

The coverage rate range is 7.4 – 9.8 m<sup>2</sup>/L, and is highly dependent on substrate texture and porosity.

**NOTE: DO NOT APPLY THICKER THAN RECOMMENDED AS THIS MAY CAUSE DISCOLOURATION AND POOR PERFORMANCE.**

## DIRECTIONS FOR USE

---

**Surface Preparation:** The surface to be sealed with **EVERCLEAR VOX** must be structurally sound, clean, and dry. **EVERCLEAR VOX** can be applied over a previous coat of acrylic concrete sealer; however, when the chemical makeup of the previous sealer is unknown, a small test section is recommended to ensure compatibility. Premixing of **EVERCLEAR VOX** is not required. Do not thin or dilute with water or any other solvent.

**Application:** Apply **EVERCLEAR VOX** in a uniform, continuous film by hand-held low pressure pump-up sprayer, short nap roller, or foam roller. When spraying, backroll over any sprayer overlap marks to ensure even coverage. Redistribute or remove puddles or excess **EVERCLEAR VOX** before it dries. Follow recommended coverage rates carefully to avoid uneven or heavy applications. For best results, two thin coats of **EVERCLEAR VOX** are recommended, with a minimum 1-2 hour interval between applications, following the prescribed coverage rates.

## REMOVAL

---

Dried, cured **EVERCLEAR VOX** may be removed with strong solvents such as acetone (always follow package directions and warning labels).

## CLEAN UP

---

Clean tools and equipment with water immediately following use. Clean drips and overspray with warm soapy water while still wet. If not cleaned immediately, the sealer may leave an unwanted residue on painted surfaces, glass or wood.

## PRECAUTIONS / LIMITATIONS

---

- Do not allow containers of this product to freeze during transport or storage. Material becomes unusable if allowed to freeze. Store between 10°C to 38°C.
- For best application results product temperature should be between 10°C to 38°C with ambient and surface temperatures between 7°C to 35°C.
- Although compatible with many carpet, tile and floor covering adhesives, a test section is recommended to ensure good bond between the adhesive and **EVERCLEAR VOX**.
- In all cases, consult the Safety Data Sheet before use.

Rev: 15/03/17