

Flowflake Terroso

An epoxy resin floor finish that contains varying sizes of flakes scattered over a pigmented base coat and finished with a clear sealer.

Ideal for use in commercial settings such as retail showrooms, designer outlets and offices.



Attractive:

A decorative floor finish that is available in a range of colour combinations.



Hard-Wearing:

Hard-wearing & abrasion resistant suitable for medium to heavy traffic.



Easy to Clean:

The seamless finish allows the system to be easily cleaned.



Minimises Visible Scratches:

Speckled flake finish disguises visible surface scratches.



Chemical Resistant:

Protects against a variety of chemicals found in commercial & industrial areas.



Black Granite



Glacier



Freckle



Frosty



Grey Granite



Moonlite



Oyster



Storm

The applied colours may differ from the examples shown.
For a full colour chart and samples, contact your local Flowcrete office.



Technical Profile*

FIRE RESISTANCE			
EN 13501-1	B _{fl} - s1		
SLIP RESISTANCE**			
Method described in BS 7976-2 (typical values for 4-S rubber slider)	Dry >40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)		
THERMAL RESISTANCE			
Tolerant of sustained temperatures up to 60°C			
WATER PERMEABILITY			
Nil - Karsten test (impermeable)			
ABRASION RESISTANCE			
BS8204:Part 2:2002	Class AR2 - Medium duty industrial and commercial		
CHEMICAL RESISTANCE			
Contact Technical Department			
FLEXURAL STRENGTH			
BS 6319	15 N/mm ²		
TENSILE STRENGTH			
BS 6319	10 N/mm ²		
BOND STRENGTH			
Greater than cohesive strength of 25 N/mm ² concrete. >1.5 MPa			
IMPACT RESISTANCE			
ISO 6272	1 kg weight >1.8 m 2 kg weight >1.5 m		
SPEED OF CURE			
	10 °C	20 °C	30 °C
Light Traffic	36 h	24 h	16 h
Full Traffic	72 h	48 h	36 h
Full Chemical Cure	12 d	7 d	6 d

* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.


**The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance, longer-term wear and/or surface contaminants (wet or dry). Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

Model Specification

System	Flowflake Terrosso
Finish	Dependant on specification
Thickness	Dependant on specification
Manufacturer	Tremco CPG Malaysia

Preparatory work and application in accordance with manufacturer's instructions.

System Design



Products Included In This System

Primer	Flowprime
Scratch Coat	Flowcoat SC (optional)
Base Coat	Flowflake Basecoat
Flake Scatter	Terrosso Flakes
Finishing Coat	Specified Topcoat*

* Topcoats may vary dependant on the environmental condition. Please consult Technical Department for more details.

Detailed application instructions are available upon request.

Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm², free from laitance, dust and other contamination. The substrate should be dry to 75% RH as per BS8204 and free from rising damp and ground water pressure.

Installation Service

The installation should be carried out by a licensed contractor with a documented quality assurance scheme. For details of our licensed contractors, contact our customer service team or enquire via our website at www.flowcreteasia.com

Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

Important Note

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages.

Further Information

To ensure you are specifying a fit-for-purpose floor, please consult our Technical Advisors or visit our website to register your interest in specifying one of the most durable floors on the market.

1. Light colours may require additional coats to achieve desired results 2. It is recommended that top coat colours are close to base coats colours to achieve desired results
3. This product is not UV stable and may discolour unless otherwise stated 4. System Data Sheet to be read in conjunction with Method Statement and Product data Sheets.