

## Peran Comfort (2-3 mm)

A self-smoothing polyurethane resin flooring system with matt-satin finish suitable for minimalist, modern, and contemporary environments.

Ideal for use in commercial settings such as retail, schools, designer outlets and offices.



### Attractive:

A contemporary floor coating that provides a smooth, matt-satin finish.



### Sound Dampening:

The cushioned surface provides a resilient and sound dampening finish.



### Low Odour:

Solvent free and low odour during and after application.



### Hard-Wearing:

Hard-wearing & suitable for intensive foot traffic in commercial settings.



### Chemical Resistant:

Protects against a variety of chemicals found in commercial areas.



Smokey Grey



Dusty Grey



Old Gold

The applied colours may differ from the examples shown.  
For a full colour chart and samples, contact your local Flowcrete office.



## Technical Profile\*

FIRE RESISTANCE			
EN 13501-1	B <sub>1</sub> - s1		
SLIP RESISTANCE**			
Method described in BS 7976-2 (typical values for 4-S rubber slider)	Dry > 40, Wet depends on specification (in accordance with HSE and UKSRG guidelines)		
THERMAL RESISTANCE			
Tolerant of sustained temperatures up to 40°C			
WATER PERMEABILITY			
Nil - Karsten test (impermeable)			
CHEMICAL RESISTANCE			
Contact Technical Department			
ELONGATION AT BREAK			
DIN 53504	50 - 100%		
SHORE A HARDNESS			
DIN 53505	Approx. 80		
BOND STRENGTH			
Greater than cohesive strength of 25 N/mm <sup>2</sup> concrete. > 1.5 MPa			
TOXICITY			
Inert and harmless when cured			
SPEED OF CURE	10 °C	20 °C	30 °C
Light Traffic	48 h	36 h	24 h
Full Traffic	96 h	48 h	36 h
Full Chemical Cure	14 d	7 d	6 d

\* These figures are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity.


\*\*The slipperiness of flooring materials can change significantly, due to the installation process, after short periods of use, due to inappropriate maintenance, longer-term wear and/or surface contaminants (wet or dry). Textured systems are recommended to meet slip resistance value requirements for wet conditions and/or surface contaminants (wet or dry) - please contact our Technical Advisors for further details and specifications.

## Model Specification

System	Peran Comfort
Finish	Matt-Satin
Thickness	2 - 3 mm
Manufacturer	Flowcrete Asia

Preparatory work and application in accordance with manufacturer's instructions.

## System Design



## Products Included In This System

Primer	Flowprime
Scratch Coat	Flowcoat SC (optional)
Base Coat	Peran Comfort
Finishing Coat	Flowseal Satin

Detailed application instructions are available upon request.

## Substrate Requirements

Concrete or screed substrate should be a minimum of 25N/mm<sup>2</sup>, free from laitance, dust and other contamination. The substrate should be dry up to 75% RH as per BS8204 and free from rising damp and ground water pressure.

## Installation Service

The installation should be carried out by a licensed contractor with a documented quality assurance scheme. For details of our licensed contractors, contact our customer service team or enquire via our website at [www.flowcreteasia.com](http://www.flowcreteasia.com)

## Environmental Considerations

The finished system is assessed as non-hazardous to health and the environment. The long service life and seamless surface reduce the need for repairs, maintenance and cleaning. Environmental and health considerations are controlled during manufacture and application of the products by Flowcrete staff and fully trained and experienced contractors.

## Aftercare, Cleaning & Maintenance

Clean regularly using a single or double headed rotary scrubber drier in conjunction with a mildly alkaline detergent.

## Important Note

Flowcrete products are guaranteed against defective materials and manufacture and are sold subject to our standard 'Warranty, Terms and Conditions of Sale', copies of which can be obtained on request. Warranty does not cover suitability, fit for purpose or any consequential or related damages.

## Further Information

To ensure you are specifying a fit-for-purpose floor, please consult our Technical Advisors or visit our website to register your interest in specifying one of the most durable floors on the market.

1. Light colours may require additional coats to achieve desired results 2. It is recommended that top coat colours are close to base coats colours to achieve desired results  
3. This product is not UV stable and may discolour unless otherwise stated 4. System Data Sheet to be read in conjunction with Method Statement and Product data Sheets.